

Security you can trust

11 Looking after the things people care about, wherever they are.

Texecom's electronic security products and services protect millions of people and properties around the world.

Texecom is leading the way with digital and cloud-based solutions, adding value and providing interoperability with wider security and building management systems - offering increasingly connected, intelligent and dynamic solutions to meet the world's future security challenges.



Contents

Digital Services	4-5
Control Panels & Communicators	6-7
Keypads	8-9
Expanders & Power Supplies	10
Control Panel Accessories	11
Motion Detectors	12-13
Perimeter Detectors	14
External Detectors	15
Safety Devices	15
External Sounders	16-17
Wireless Kits	18-19
Product Branding	20-21
Product Compliance	22-23

Product feature key:



EN50131 Grade 2



EN50131 Grade 3



Ricochet® wireless mesh technology



System Users

Interact, control and integrate your Premier Elite security system like never before. Texecom Connect lets you take direct control of your alarm system from a tablet or smartphone device - from anywhere in the world.

Learn more >







Modes



Devices





Alarm Companies

Texecom Cloud provides your business the tools to manage, configure and control your alarm system and Texecom Connect app portfolio.

Learn more >



End User App Management



p Remote It Maintenance



System Programming



Access Anywhere






Engineers

Make sure your field engineers and technicians have downloaded TexecomPro, the free app for iOS and Android that provides support and product information all at the touch of a button.

Learn more >





Training

Texecom Academy provides a variety of courses, from beginner to expert, to give installers the technical expertise needed to maximise the benefits of Texecom alarm systems.

Learn more >





What you need

Signed up for all the digital services on offer? Great. Now you'll need to make sure your system is connected in order to maximise the value to you and your business. Choose from our range of connectivity options, and make sure your system is compatible with Texecom's digital suite.

Premier Elite alarm system



SmartCom communicators



Texecom Cloud account



Security Control Systems

Communicating control panels

The Premier Elite Series provides a single, comprehensive system architecture and peripheral range that scales from the simplest and smallest security applications through to the largest and most complex.

Featuring a common programming platform, interoperable wired and wireless peripheral devices, design flexibility and integration capabilities, the Premier Elite Series provides a high performance security solution for applications around the world

Common programming platform

Each Premier Elite control panel shares the same programming platform and peripheral devices, ensuring instant product familiarity across the range.



Greater scalability

Premier Elite control panels can accept multiple *Ricochet* capable wireless expanders increasing the wireless device capacity.



SmartCom communications

Communicating exclusively using outbound connections, SmartCom communicators remove the need to open any router ports, ensuring simplicity of installation and maximum security.



Control Panels & Communicators

Premier Elite 24

Panel expandable to 24 zones

Premier Elite 48

Panel expandable to 48 zones

Premier Elite 88

Panel expandable to 88 zones

Premier Elite 168

Panel expandable to 168 zones

Premier Elite 640

Panel expandable to 640 zones



G³

Premier Elite 24 (Polymer) Panel expandable to 24 zones





Premier Elite 64-W LIVE

Self contained wireless panel expandable to 64 wireless zones



Premier Elite 64-W

Wireless panel expandable to 64 wireless zones





SmartCom

Ethernet and WiFi communicator

 Communicator for connecting Premier Elite systems to Texecom Connect and Texecom Cloud



SmartCom 4G UK only Ethernet and WiFi 4G communicator

- SmartCom with added 4G connectivity for cellular or dual path connectivity
- Onboard eSIM offers global roaming access and service subscription through Texecom Cloud



Control Panel	Max Zones (Expanded)	Max Wireless Zones (Expanded)	Hard Wired Onboard	Wireless Onboard	Areas	Max Keypads	User Codes	EN Grade
Premier Elite 24	24	16	8	-	2	4	25	PD6662, EN50131-3, Grade 3 Class II
Premier Elite 24 (Polymer)	24	16	8	-	2	4	25	PD6662, EN50131-3, Grade 2 Class II
Premier Elite 48	48	32	8	-	4	4	50	PD6662, EN50131-3, Grade 3 Class II
Premier Elite 64-W	76	64	4	32	4	4	50	PD6662, EN50131-3, EN50131-5-3 Grade 2 Class II
Premier Elite 64-W LIVE	74	64	4	32	4	4	50	PD6662, EN50131-3, EN50131-5-3 Grade 2 Class II
Premier Elite 88	88	64	8	-	8	8	100	PD6662, EN50131-3, Grade 3 Class II
Premier Elite 168	168	128	8	-	16	16	200	PD6662, EN50131-3, Grade 3 Class II
Premier Elite 640	640	512	0	-	64	64	1000	PD6662, EN50131-3, Grade 3 Class II

Keypads



Range of surface finishes

The Premier Elite keypads compliment any environment with a selection of surface finishes including:Diamond Black, Gunmetal, Polished Chrome, Satin Chrome, Polished Brass & Polymer (FMK only).

Spot the difference

The Premier Elite LCDLP-W is all but identical to its wired equivalent - in size, aesthetics and performance. The only difference is wireless connectivity powered by *Ricochet* mesh technology, the world's most robust wireless security technology.



SmartKey with prox

The Premier Elite SmartKey features a replaceable battery and an integral RFID proximity tag. The RFID proximity tag is ideal for use with compatible keypads, freeing up the wireless keyfob to control outbuildings or to act as a dedicated panic alarm.



Surface and flush mount metal keypads



Premier Proximity Keytag Proximity tags - pack of 5



Premier Elite LCDLP

Large LCD screen keypad with prox



Premier LCDP/LCDLP

Small/large LCD screen keypad with prox







Premier Elite LCDLP-W

Wireless large LCD screen keypad with prox





Premier Elite SmartKey

Wireless iconic keyfob with prox

- Remote arm, part arm and disarm
- Alarm system status display
- Typical 2 to 3 year battery life
- Output control



Keypad	Premier Elite Series Compatible	Premier Series Compatible	Display	Touchtone Keys & Backlighting	Additional Zones	Programmable Outputs	Extension Speaker	En Grade
Premier Elite FMK	•	•	Large Blue LCD	•	2	1	•	EN50131-1, EN50131-3 Grade 3 Class II
Premier Elite SMK	•	•	Large Blue LCD	•	2	1	•	EN50131-1, EN50131-3 Grade 3 Class II
Premier Elite LCDLP	•	•	Large Blue LCD	•	2	1	•	EN50131-1, EN50131-3 Grade 3 Class II
Premier Elite LCDLP-W	•		Large Blue LCD	•	0	0	•	EN50131-1, EN50131-3, EN50131-5-3 Grade 2 Class II
Premier LCDP	•	•	Green LCD	•	2	1		EN50131-1, EN50131-3 Grade 3 Class II
Premier LCDLP	•	•	Large Green LCD	•	2	1	•	EN50131-1, EN50131-3 Grade 3 Class II

Expanders & Power Supplies

Premier Elite 8XP

8 zone expander

- 8 Additional Outputs
- 1 Auxiliary Input
- Speaker Driver
- · Grade 3, Class II





Premier Elite 8XP-W

8 zone wireless expander

- Wireless Monitor Software Diagnostics
- Engineers Keypad Connectivity
- EN50131-3. EN50131-5-3 Grade 2 Class II





32 zone wireless expander

 Wireless Monitor Software Diagnostics

Premier Elite 32XP-W

- Engineers Keypad Connectivity
- EN50131-3. EN50131-5-3 Grade 2 Class II







Premier Elite 60iXD

Expansion module

- 60 Additional Zones
- Remote Wired
- Plug-On (Local mode & Network mode)
- · Expansion module providing two iD loops each supporting 30 iD biscuits





Premier Elite RM8 Relay module

- · 8 Relay Outputs
- Remote Wired
- Plug-On Premier Elite Series Only (except Premier Elite 24)





Premier 8XE

Plug-on 8 zone expander

- · Local plug-on Zone Expander for use with Premier Elite 24 control panels
- Additional 8 programmable EOL zones









Switch mode power supply

- Energy efficient 2.5A switch mode power supply with Premier Elite 8XP expander
- · Full monitoring & Diagnostics with Premier Elite Control Panels
- · Grade 3, Class II





Premier Elite PSU200

Switch mode power supply

- Energy efficient 2.5A switch mode power supply
- · Grade 3, Class II









Control Panel Accessories

Premier Elite TTLCom

Network to fibre optic TTL converter

• Converts network signals to TTL, and vice versa



Premier Elite ComPort+ Plug-on PCB

- Converts the on-board digital communicator connector on Premier Elite 24-168 into serial communications port ComPort 3
- Allows three serial communication ports to be used simultaneously for use with compatible products



Premier Elite USB Com USB interface connector

- Connection between control panel and PC
- · Local upload/download



Premier Elite PC Com

Serial interface connector

- Connection between control panel and PC
- Local upload/download



Premier Elite Flasher Interface

Flasher interface

• Update the Premier Elite Control Panel firmware



Access control

Premier Elite iProx

· Can be used as a single door access controller



Premier Flite External iProx Coil

- For use with Premier Elite iProx and Texecom Proximity Tags
- Allows the user to disarm the alarm system externally



Detectors

All your motion detection needs. Captured.

A security system is only as good as its ability to detect. Your reputation, your business, your future, and your customers' wellbeing, all depends on making the right choice of motion detection.

Texecom's new range of motion detectors, Capture, is our highest performing, most reliable, easiest to install range of detectors, ever.



Double the detection

Each Capture model features double the number of detection points compared to previous Texecom detectors.



True 360°pickup

All Capture ceiling mount models use omni-directional quad element PIR sensing for true 360°pickup.



Compliant coverage

Unlike many other manufacturers, the entire coverage pattern is independently certified to EN50131-2.



Wall mount:

Capture P15 15m PIR

Capture Q20 20m Quad PIR

Capture D20 20m Dual Tech



Capture CD



Wall mount:

Capture P15-W Wireless 15m PIR

Capture Q20-W Wireless 20m Quad PIR

Capture D20-W Wireless 20m Dual Tech



Capture A20 20m Anti-Masking Dual Tech

Wall mount:



Capture CQ Ceiling Mount Quad PIR

Ceiling Mount Quad Dual Tech



Ceiling mount:

Capture CQ-W Wireless Ceiling Mount Quad PIR

Capture CD-W Wireless Ceiling Mount Quad Dual Tech



Ceiling mount:

Capture CA Ceiling Mount Quad Anti-Masking Dual Tech



Model	Part No.	Description	Mounting	EN Grade	Pyro	Microwave	Anti- masking	PetWise Mode	CloakWise Mode	Dual Tech Mode	Low Sensitivity	Range	Coverage	Mounting Height	LED
P15	AKB-0001	15m PIR	Wall	G2	Dual			•				15m	90°	1.5m - 3m	Cyan
Q20	AKC-0001	20m Quad PIR	Wall	G2	Quad			•				20m	90°	1.5m - 3m	Cyan
D20	AKD-0001	20m Dual Tech	Wall	G2	Quad	•		•	•	•		20m	85°	1.5m - 3m	Tri-Colour
cq	AKF-0001	Ceiling Mount Quad PIR	Ceiling	G2	Quad						•	9.3m	360°	2.4m - 3.6m	Cyan
CD	AKG-0001	Ceiling Mount Quad Dual Tech	Ceiling	G2	Quad	•			•	•	•	9.3m	360°	2.4m - 3.6m	Tri-Colour
P15-W	GDA-0001	Wireless 15m PIR 868MHz	Wall	G2	Dual			•				15m	90°	1.5m - 3m	Tri-Colour
Q20-W	GDB-0001	Wireless 20m Quad PIR 868MHz	Wall	G2	Quad			•				20m	90°	1.5m - 3m	Tri-Colour
D20-W	GDC-0001	Wireless 20m Dual Tech 868MHz	Wall	G2	Quad	•		•	•	•		20m	85°	1.5m - 3m	Tri-Colour
CQ-W	GDD-0001	Wireless Ceiling Mount Quad PIR 868MHz	Ceiling	G2	Quad						•	9.3m	360°	2.4m - 3.6m	Tri-Colour
CD-W	GDE-0001	Wireless Ceiling Mount Quad Dual Tech 868MHz	Ceiling	G2	Quad	•			•	•	•	9.3m	360°	2.4m - 3.6m	Tri-Colour
A20	AKE-0001	20m Anti-Masking Dual Tech	Wall	G3	Quad	•	•		•	•	•	20m	85°	1.5m - 3m	Tri-Colour
CA	AKH-0001	Ceiling Mount Quad Anti-Masking Dual Tech	Ceiling	G3	Quad	•	•		•	•	•	9.3m	360°	2.4m - 3.6m	Tri-Colour

Perimeter Detectors

Impag S

Shock sensor

- VIBER™ Accelerometer Technology
- · Digital Signal Processing
- 5 Selectable Digital Sensitivity Settings
- Available in White, Brown and Grey
- EN 50131-2-8 Grade 2







Premier Elite Micro Shock-W

Miniature Wireless Shock Sensor

- Small size 57mm x 27.5mm x 8.2mm
- Superior accelerometer technology
- 3 colour options: White, Brown & Grey
- LED assisted setup procedure
- 3 Year typical battery life
- EN50131-2-8 Grade 2





Impaq SC

Shock and contact sensor

- VIBER™ Accelerometer Technology
- · Digital Signal Processing
- 5 Selectable Digital Sensitivity Settings
- · Available in White, Brown and Grey
- EN 50131-2-8 Grade 2







Premier Elite Micro Contact-W

Miniature Wireless Magnetic Contact

- Small size: 57mm x 27.5mm x 8.2mm
- 4-Year typical battery life
- 3 colour options: White, Brown & Grey
- LED assisted setup procedure
- EN50131-2-6 Grade 2





Premier Impaq Glass Break Acoustic glass break sensor

- Suited for plate, tempered, laminated & wired glass types
- Adjustable sensitivity
- Detection/disable/comfort LED
- Microprocessor technology
- EN 50131 Grade 2





VIBER™ Accelerometer Technology

- Digital Signal Processing
- Roller Shutter Input for 'Partly Open' Protection
- · Available in White, Brown and Grey
- EN50131-2-8 Grade 2
- EN50131-2-6 Grade 2

















External Detectors

Premier External TD

Non-overlapping twin mirrored PIR

- · Adjustable optics and adjustable sensitivity
- Digital temperature compensation
- IP65 sealed enclosure
- Day/night mode and high white light immunity
- Mounting height: 1.0-1.4m
- Pole bracket available separately
- EN 50131 Grade 2





Premier External TD-W

Wireless external detector

- Non-overlapping Twin Mirrored PIR Optics
- IP65 sealed enclosure
- Selectable 12m/8m/5m/2m Range
- 90° Coverage Rotatable through 180°
- Perfect for Security / Lighting / Gates etc.







Safety Devices

Premier Elite PA DP-W

Wireless Double Push Panic Alarm

- Joint Venture with Elmdene
- Typical 2 to 3 Year Battery Life
- Suitable for Commercial Applications





Premier Elite OH-W


Wireless Optical & Heat Fire Detector

- Joint Venture with Apollo
- 1.5 Year Battery Life
- Built-in 85dB(A) Sounder





External Sounders



Odyssey X backplates are complemented by a series of cover options in X1 and X3 forms. X1 and X3 covers come complete with integral backlight compatibility.



Available directly from Texecom, these photo quality custom designed graphic inserts replace traditional screen printing, enhancing quality and removing the need to stock custom screen printed covers.

Choice of illuminated, non-illuminated, wired, wireless & dummy versions.



Backplates

Odyssey X-BE

Grade 2 sounder with integral backlight

- 109dB (A) piezo sounder
- · Wall & cover tamper
- Patented engineer hold-off mode
- · Alternating white LED indication
- Grade 2 Class IV



Odyssey X-E

Grade 2 sounder

- 109dB (A) piezo sounder
- · Wall & cover tamper
- Patented engineer hold-off mode
- · Alternating white LED indication
- · Grade 2 Class IV



Odyssey X-W

Wireless sounder

- 105dB (A) piezo sounder
- · Wall & cover tamper
- Selectable comfort LEDs
- · Ricochet® mesh technology
- 8 x AA lithium batteries included
- Grade 2. Class IV

Odyssey X-D Dummy sounder

- No electronics included
- Imitation sounder
- · Low cost deterrent
- Accepts X1 and X3 covers



Grading N/A

Odyssey X-B

Grade 3 sounder with integral backlight

- 115dB (A) twin piezo sounder
- · Wall & cover tamper
- Patented engineer hold-off mode
- · Battery monitoring with fault output
- Alternating white LED indication
- Grade 3 Class IV



Odyssey X

Grade 3 sounder

- 115dB (A) twin piezo sounder
- · Wall & cover tamper
- Patented engineer hold-off mode
- · Battery monitoring with fault output
- Alternating white LED indication
- · Grade 3 Class IV



Covers

Odyssey X1 Cover

Vertically mounting external sounder

- White or black frame option
- Lens colour options: blue, red, white & green
- Integral backlight compatibility
- Photo quality graphic insert compatibility



Odyssey X3 Cover

Hexagonal external sounder


- White or black frame option
- Lens colour options: blue, red, white & green
- Integral backlight compatibility
- Photo quality graphic insert compatibility





Wireless Kits





Common programming platform

Each Premier Elite control panel shares the same programming platform and peripheral devices, ensuring instant product familiarity across the range.



Wireless connectivity

Ricochet enabled wireless devices receive and repeat wireless transmissions from other devices. The size, scalability and range of the entire system are extended as wireless signalling is no longer limited by point-to-point communications.



Includes Capture

Texecom's new range of motion detectors, Capture, is our highest performing, most reliable, easiest to install range of detectors, ever.



64 Zone Wireless Kit

- 1 x Premier Elite 64-W
- 5 x Premier Proximity Tags
- 1 x Premier Elite LCDLP-W
- 3 x Capture P15-W



64 Zone Self-Contained Wireless Kit

- 1 x Premier Elite 64-W LIVE
- 2 x Premier Elite SmartKey
- 3 x Capture P15-W
- 1 x Premier Elite Micro Contact-W
- 1 x Odyssey X-W Backplate







64 Zone Wireless Kit

- 1 x Premier Elite 64-W
- 5 x Premier Proximity Tags
- 1 x Premier Elite LCDLP-W
- 3 x Capture P15-W
- 1 x Premier Elite Micro Contact-W
- 1 x Odyssev X-W Backplate



32 Zone Hybrid Wireless Kit

- 1 x Premier Elite 48
- 1 x Premier LCDP
- 5 x Proximity Tags
- 1 x Premier Elite 32XP-W
- 2 x Capture Q20-W
- 2 x Capture D20-W
- 2 x Impaq SC-W





64 Zone Self-Contained Wireless Kit





• 3 x Capture P15-W

• 1 x Premier Elite Micro Contact-W



64 Zone Wireless Kit

- 1 x Premier Elite 64-W
- 5 x Premier Proximity Tags
- 1 x Premier Elite LCDLP
- 3 x Capture P15-W
- 1 x Premier Elite Micro Contact-W







Product Branding

You specify the best equipment. You design the innovative security solution. You make your customer's lives and livelihoods safer.

Isn't it time you took the credit?

With Texecom you can. The Texecom Product Branding Scheme ensures your company logo and contact details are given maximum exposure.

Selected Texecom products are available with a designated installer branding position which allows you to introduce your own personalised company emblem, elevating your profile in a professional and quality manner.

How to order >



Domed emblems

Personalised company emblems are custom made by Texecom and available as a pack of 80 emblems for use on a variety of Texecom products, including keypads, control panels and expanders.



Odyssey X inserts

Available directly from Texecom, these photo quality custom designed graphic inserts replace traditional screen printing, enhancing quality and removing the need to stock custom screen printed covers.



Capture inserts

Wall mount Capture models feature a new innovative graphic insert for ultimate installer branding.



Product Branding









Product Compliance

Product Compliance Tables

All Texecom products are designed to meet or exceed all relevant international security standards.

For territory specific standard requirements please contact a member of the Texecom sales team.

Control Panels	
Premier Elite 24 Polymer	EN50131-1, EN50131-3 Grade 2 Class II
Premier Elite 24 Metal	EN50131-1, EN50131-3 Grade 3 Class II
Premier Elite 48	EN50131-1, EN50131-3 Grade 3 Class II
Premier Elite 64-W	EN50131-1, EN50131-3, EN50131-5-3 Grade 2 Class II
Premier Elite 64-W LIVE	EN50131-1, EN50131-3, EN50131-5-3 Grade 2 Class II
Premier Elite 88	EN50131-1, EN50131-3 Grade 3 Class II
Premier Elite 168	EN50131-1, EN50131-3 Grade 3 Class II
Premier Elite 640	EN50131-1, EN50131-3 Grade 3 Class II

Communicators	
Texecom Connect SmartCom	EN50131-1, EN50136-2 Grade 2 Class II SP3
Texecom Connect SmartCom 4G	EN50131-1, EN50136-2 Grade 2 Class II SP3

Keypads	
Premier Elite LCDLP	EN50131-1, EN50131-3 Grade 3 Class II
Premier Elite LCDLP-W	EN50131-1, EN50131-3, EN50131-5-3 Grade 2 Class II
Premier Elite FMK	EN50131-1, EN50131-3 Grade 3 Class II
Premier Elite SMK	EN50131-1, EN50131-3 Grade 3 Class II
Premier LCDP	EN50131-1, EN50131-3 Grade 3 Class II
Premier LCDLP	EN50131-1, EN50131-3 Grade 3 Class II
Premier Elite SmartKey	EN50131-1, EN50131-5-3 Grade 2 Class II

Expanders	
Premier Elite 60IXD	EN50131-1, EN50131-3 Grade 3 Class II
Premier Elite 8XP	EN50131-1, EN50131-3 Grade 3 Class II
Premier Elite RM8	EN50131-1, EN50131-3 Grade 3 Class II
Premier Elite 8XP-W	EN50131-1, EN50131-3, EN50131-5-3 Grade 2 Class II
Premier Elite 32XP-W	EN50131-1, EN50131-3, EN50131-5-3 Grade 2 Class II

Power Supplies	
Premier Elite PSU200	EN50131-1, EN50131-3, EN50131-6 Grade 3 Class II
Premier Elite PSU200XP	EN50131-1, EN50131-3, EN50131-6 Grade 3 Class II

Motion Detectors	
Capture P15	EN50131-1, EN50131-2-2 Grade 2 Class II
Capture Q20	EN50131-1, EN50131-2-2 Grade 2 Class II
Capture D20	EN50131-1, EN50131-2-4 Grade 2 Class II
Capture CQ	EN50131-1, EN50131-2-2 Grade 2 Class II
Capture CD	EN50131-1, EN50131-2-4 Grade 2 Class II
Capture P15-W	EN50131-1, EN50131-2-2 Grade 2 Class II
Capture Q20-W	EN50131-1, EN50131-2-2 Grade 2 Class II
Capture D20-W	EN50131-1, EN50131-2-4 Grade 2 Class II
Capture CQ-W	EN50131-1, EN50131-2-2 Grade 2 Class II
Capture CD-W	EN50131-1, EN50131-2-4 Grade 2 Class II
Capture A20	EN50131-1, EN50131-2-4 Grade 3 Class II
Capture CA	EN50131-1, EN50131-2-4 Grade 3 Class II

Perimeter Detectors	
Impaq S	EN50131-2-8 Grade 2 Class II
Impaq SC	EN50131-2-8, EN50131-2-6 Grade 2 Class II
Impaq SC-W	EN50131-2-8, EN50131-2-6, EN50131-5-3 Grade 2 Class II
Premier Elite Micro Contact-W	EN50131-1, EN50131-2-6, EN50131-5-3 Grade 2 Class II
Premier Elite Micro Shock-W	EN50131-1, EN50131-5-3, EN50131-2-8 Grade 2 Class II
Premier Impaq Glass Break	EN50131-1, TS50131-2-7-1 Grade 2 Class II

External Detectors	
Premier External TD	N/A
Premier External TD-W	EN50131-5-3 Grade 2 Class IV

Safety Devices	
Premier Elite PA DP-W	EN50131-1, EN50131-5-3 Grade 2 Class II
Premier Elite OH-W	EN50131-1, EN50131-5-3 Grade 2 Class II

External Sounders	
Odyssey X-B	EN50131-4 Grade 3 Class IV
Odyssey X	EN50131-4 Grade 3 Class IV
Odyssey X-BE	EN50131-4 Grade 2 Class IV
Odyssey X-E	EN50131-4 Grade 2 Class IV
Odyssey X-W	EN50131-4, EN50131-5-3 Grade 2 Class IV



Locations

Head Office

St. Crispin Way Haslingden Lancashire BB4 4PW England

Injection Moulding Facility

Slackcote Lane Delph Oldham OL3 5TW England

India Office

Halma India Prestige Shantiniketan 7th Floor, Tower C Whitefield Main Road Bengaluru 560048 India

China Office

Kuntai International Mansion Building 1 YiNo.12 ChaoWai Street Chao Yang District Beijing PRC 100020 China



Head Office

St. Crispin Way Haslingden Lancashire BB4 4PW | England

Phone +44 (0)1706 220460 Email sales@texe.com Web www.texe.com

